



www.gst.uk.com  
info@gst.uk.com

## Motorized Valve HW-G3 Series



### Features

- Forging brass body
- Stainless steel base, aluminum enclosure
- Driven by hermetic unidirectional hysteresis synchronous motor, stainless steel spring reset
- Low power consumption and noise
- Connecting driver and valve body with buckles, ensuring an easy and convenient installation and disassembly

### Technical Specification

Power supply voltage: 220VAC±10%, 50/60 Hz

Self consumption : less than 7W

Nominal pressure: 1.6 MPa

Type of connection: According to BSPP (British Standard for Parallel Pipe) , NPT (American Standard Pipe Taper Thread )

Operating Time: ON : less than 10s, OFF : less than 6s

Medium temperature : 5°C--90°C

### Ordering Information:

Part No	Description
GST-G2-1/2-S2	Motorized Valve, For 1/2" pipe size
GST-G2-3/4-S2	Motorized Valve, For 3/4" pipe size
GST-G2-1-S2	Motorized Valve, For 1" pipe size

**GST England** Lion Court, Staunton Harold Hall, Melbourne Road, Ashby de la Zouch, Leicestershire, England LE65 1RT Tel: +44 1283 225 478 Fax: +44 1283 220 690

**GST Dubai** ZA04, Jebel Ali Free Zone, P.O.Box 17998, Dubai UAE  
Tel: +971 (0)4 8833 050 Fax: +971 (0)4 8833 053

**GST China** 80, Changjiang East Road, Economic & Technology Development Zone Qinhuangdao, Hebei, China Tel: +86(0)335 850 2383 Fax: +86 (0)335 850 7588