



Sprinkler Indication Panel

GST-SIP

Description

GST-SIP Sprinkle Indication Panel is a monitoring panel intended for use with sprinkler extinguishing system. The main function is to monitor the zones or areas of fire situation, status and condition of the pump, water level and give the appropriate visible indication.

The control panels have built with RS 485 interface provides to have software interface to any GST intelligent fire panel. The Sprinkler Indication display board is fixed to internal chassis by screw for easy removal or 19" system rack.

Features and Benefits

1. Manufactured for any particular project to suit specific customer requirement.
2. LED status indication
3. RS 485 interface
4. Optional Reset Panel
5. Optional Alarm Sounder
6. Optional Sounder Silence

Technical Specifications

- Display Range: 1 up to 100 group code points. The code supports the mode of wildcard character, expandable according to client requirement.
- Wiring: Connected with fire alarm controller with two polarized wires; connected with power supply with two 24VDC power lines, non-polarized.
- Monitoring Current $\leq 25\text{mA}$
- Alarming Current $\leq 100\text{mA}$
- Environment Temperature: $0^{\circ}\text{C}+40^{\circ}\text{C}$
- Relative Humidity: $\leq 95\%$, non condensing
- Power: Centralized power supply by 18VDC-28VDC, static state power consumption $\leq 0.7\text{W}$, maximal power consumption $\leq 3\text{W}$
- Dimension: custom made/ unspecified

Ordering Information



Part Number: GST-SIP
Description: Intelligent Sprinkler Indication Panel
Pack Qty. per Box: 1

